






Fast, powerful, and precise: discover a machine unique in the market. The ISx000 range is designed for large format jobs to batch engraving and cutting.



#### **HIGH-PERFORMANCE**

Developed from a monobloc structure the ISx000 range is a solid workhorse. A choice between 4 high frequency motors means that you will be working with the highest performance whatever the material or its thickness.

#### **VALUE FOR MONEY**

These large format engraving machines makes high volume jobs quicker and easier, The ISx000 range remains unrivalled on the ratio, price per working area, on the market. Once you have set up the job on Gravostyle, you can trust the machine to do the task in all safety without your constant supervision.

#### **ADAPTABLE**

3 different sizes, 2 motorized axis (stepper or brushless motors) and a large range of accessories. Light and deep engraving, batch labelling, drilling, and 2.5 milling (hot iron) the ISx000 range is versatile enough to be used in most industrial applications.



### KEY FEATURES



### ADA and braille sign engraving machine

With our ADA compliant braille solution, the ISx000 range becomes the sign maker machine.

From Gravostyle  $^{\text{TM}}$  transcribing text to braille, the machine drills the plates and lays the beads automatically.

The process is simple, hassle free and braille certified.



## Batch Engrave For High Productivity

The large marking area is designed to both engrave big items, one by one or to do batches of hundreds of smaller items at one time; use the Stamp Mode to engrave different designs, use the Matrix Mode to duplicate patterns on labels.



# 2,5 D engraving and drilling


Be it for hot stamp, insert manufacturing and even anti-counterfeit deep marking firearms, the ISx000 range will become your go to solution.

Harder metals can be processed by adding a lubrication kit, powerful spindle and the right cutting tools.





# **APPLICATIONS**



Badges, tags engraving & cutting



Front panel



Industrial milling & deep engraving



Braille ADA



2.5 D



Large letters cutting - Signage

# MATERIAL CHARACTERISTICS


|           |                        | ROTARY   | SCRIBING/DIAMOND |
|-----------|------------------------|--|------------------|
|           | Wood                   | <b>\$</b> 0 <b>•</b>   |                  |
|           | Glass, crystal         | •  |                  |
| sis.      | Leather                | <b>\$</b> \(\)   |                  |
| Materials | Stone, granite, marble | <b>•</b>   |                  |
| Σ         | Food                   | •  |                  |
|           | Ceramic                | •  |                  |
|           | Plastics               | <b>\$</b> \tilde{\tilie}\tilde{\tilde{\tilde{\tilde{\tilde{\tilde{\tilde{\tilde | •                |
|           | Metal                  | <b>\$</b>  | •                |

Cutting = Engraving / Deep marking = Marking / Etching =



#### SOFTWARE

#### **GRAVOSTYLETM**



#### Expert software made by engravers for engravers

Gravostyle<sup>TM</sup> is a professional engraving and cutting software that puts Gravotech engraving expertise in reach. Benefit from advanced possibilities and save time! Unique features available: Braille, Photostyle, Print & Cut, and more.

#### Complete engraving process mastered

Due to our history of making engraving machines, we have a full understanding of the engraving process. Gravostyle<sup>TM</sup> is fully compatible with all of our technologies. The software/machine interaction streamlines and improves your day-to-day engravings with functions like Point & Shoot.

### Gravostyle™: unique software for laser and rotary

Are you already using Gravostyle<sup>™</sup> on your rotary machine, and expanding your business with a laser? No need to learn how to use another software, switch in one click on the Gravostyle<sup>™</sup> interface to set-up laser engraving!

#### SERVICE & SUPPORT



## Training

Our training modules are designed to optimize your use of our solutions and are available for our full range of machines, software and accessories.



## Technical support

We bring you local support in your language in more than 50 countries, where we have established presence directly and with our distribution partners.



#### Maintenance

Thanks to experience gathered with Gravograph and Technifor and our global presence in more than 50 countries with 150 Gravotech technicians and our distributor partners, we can offer you a wide range of services.

# TECHNICAL DATA

|                          | IS6000  | IS7000   | IS8000                                 |  |  |
|--------------------------|---|--|--|--|--|
| Technology               | Rotary, scribing  |  |  |  |  |
| Marking area max (L x H) | 610 x 410 mm (24 x 16 in)   | 610 x 815 mm (24 x 32 in)                              | 610 x 1220 mm (24 x 48 in)             |  |  |
| Max object size          | Unlimited x unlimited x 80 mm (3.15 in)                                       |  |  |  |  |
| Max object weight        | 40Kg - 88,2 lbs   |  |  |  |  |
| Dimensions (L x W x H)   | 1093 x 1015 x 735 mm (43 x 40 x 29 in)  | 1093 x 1420 x 735 mm (43 x 56 x 29 in)                 | 1093 x 1825 x 735 mm (43 x 72 x 29 in) |  |  |
| Machine weight           | 168 kg (370 lbs)  | 220 kg (485 lbs)                                       | 265 kg (584 lbs)                       |  |  |
| Spindle power            |   | 90 W or 200 W<br>Optional spindles : 150 W, 750 W, 1kW |  |  |  |
| Type of spindle          |   | Top load spindle or collet spindle                     |  |  |  |
| Noise                    | 80 dB (A) +/- 2   |  |  |  |  |
| Point & shoot            |   | yes  |  |  |  |
| Operating temperature    |   | 5 °C (41 °F) - 40 °C (104 °F)                          |  |  |  |
| Connection to computer   |   | USB  |  |  |  |
| Maximum speed            |   | IQ : 25 mm/s (1 in/s)<br>XP : 60 mm/s (2,4 in/s)       |  |  |  |
| Z stroke (Z travel)      |   | 80 mm (3.15 in)  |  |  |  |
| Max rotation speed       |   | 20 000 rpm   |  |  |  |
| Tool diameter            | 4,36 mm (0,2 in)<br>With optional spindle : 3mm (0,1 in) to 6,36 mm (0,25 in) |  |  |  |  |





contact@gravotech.com +33 (0) 4 78 55 85 50 www.gravotech.com

**GRAVOTECH MARKING**466 rue des Mercières - Z.I. Perica
69140 Rillieux-la-Pape
France

### Distributed by:

| i e e e e e e e e e e e e e e e e e e e  |  |
|--|--|
|  |  |
|  |  |
| i  |  |
|  |  |
|  |  |
| i  |  |
| !  |  |
|  |  |
|  |  |
| I control of the cont |  |
|  |  |
|  |  |
| i e e e e e e e e e e e e e e e e e e e  |  |
|  |  |
|  |  |
| i  |  |
|  |  |
|  |  |
|  |  |
| !  |  |
|  |  |
| i  |  |
| !  |  |
|  |  |
| LL   |  |
|  |  |

Follow us:







